

## F0760 PRODUCT INFO



The COLDTAINER product line includes a large range of state of the art 12V active mobile refrigerated containers. The containers are produced using the rotational molding technology according to the highest standards. They come in a variety of types, internal volumes and internal temperature ranges designed to satisfy all possible demands of professional users in term of temperature controlled transport

- Internal gross capacity 760 litres
- Single piece design is sturdy, durable and lightweight, with no junctions or cold bridges. Made of food grade polyethylene (PE), UV stabilized. Ultra-thick insulation made by PU foam. Designed for an easy cleaning and disinfection
- Direct current cooling units designed for years of use on board of vehicles, providing low energy consumption and resistance to vibrations. Ambient temperature range from  $-20^{\circ}\text{C}$  up to  $+55^{\circ}\text{C}$  (with reduced specifications)
- Refrigeration system includes BD series 12V compressors, large surface roll-bond evaporators, ventilated high efficiency spiral tube condensers, electronic thermostat with digital display, battery protection system.
- Versions with automatic cooling / heating operation are available for the safe transport of sensitive products (i.e. pharmaceuticals, vaccines, blood). They maintain consistent temperature with a smooth air flow distribution, regardless of outside ambient temperature in alignment with GDP.
- AC/DC power supplies (input voltage 100-240Vac 50-60 Hz) available as accessories.

### Available versions:

- NDN down to  $+0^{\circ}\text{C}$
- NDH from  $+30^{\circ}\text{C}$  to  $+0^{\circ}\text{C}$
- FDN down to  $-21^{\circ}\text{C}$
- NDH from  $+30^{\circ}\text{C}$  to  $-21^{\circ}\text{C}$



**easy cooling, smart moving**

[www.coldtainer.com](http://www.coldtainer.com)

## F0760 PRODUCT INFO

Model name	F0760/NDN	F0760/NDH	F0760/FDN	F0760/FDH
EE article nr.	816020/00	816020/02	816020/01	816020/03
Gross volume (Liters)	760	760	760	760
Temperature range (°C)	+0 °C	+30 °C a +0 °C	-21 °C	+30 °C a -21 °C
Automatic cooling/heating	-	SI	-	SI
Voltage	12-24 Vdc	12-24 Vdc	12 Vdc	12 Vdc
Peak Amps (@12Vdc)	18A	18A	25A	25A
External dimensions (mm)	820 x 1420 x 1580	820 x 1420 x 1580	820 x 1420 x 1580	820 x 1420 x 1580
Weight (kg)	157	162	165	169
PU insulation (mm)	100	100	100	100
"K" insulation factor	0,35W/m²K	0,35W/m²K	0,35W/m²K	0,35W/m²K
Compressor (model)	BD80 F	BD80 F	BD220 CL	BD220 CL
Refrigerant gas (type)	R134a	R134a	R404a	R404a
Refrigerant gas (grams)	0,135	0,135	0,25	0,25
Cut-out / cut-in voltage	9,6Vdc-10,9Vdc	9,6Vdc-10,9Vdc	11Vdc-12,3Vdc	11Vdc-12,3Vdc
AC/DC power supply (opt)	560020/00	560020/00	560021/00	560021/00
AC/DC power supply input	IN 110-240Vac 50-60 Hz /Out 12Vdc	IN 110-240Vac 50-60 Hz /Out 12Vdc	IN 110-240Vac 50-60 Hz /Out 12Vdc	IN 110-240Vac 50-60 Hz /Out 12Vdc

\*with ambient temperature +30°C

(E57) 10R-060148

